

Nobelex® 1200

Technical
Information



Booster Sensitive Emulsion Explosive



Product Description

NOBELEX® 1200 is a booster sensitive explosive *derived* from mixing Anfo with emulsion. Due to high volume of gaseous products of detonation, it creates an efficient thrust on rock formation. It is water resistant and has higher density compared to water, as a result it sinks and replaces the water at the bottom of hole. Soft form of the explosive enables complete filling the bottom of hole, where the rock breakage is most difficult, and therefore, resulting in better fragmentation and higher rock yield per blast. In holes with little water, NOBELEX® 1200 enables the utilization of Anfo at upper parts of holes. It is not affected by temperature changes. NOBELEX® 1200 can suitable both bulk emulsion and cartridge.

Application Recommendations

Widely used as the main explosive for bottom and column charge for the following applications:

- In all types of blasting operations, wet and dry holes, hard formation in metal mining, in raw material and limestone quarries of cement industry, in stone quarries, highway blasting operations, at dam projects and trench blasting.
- As the bottom and column charge explosive in special blasting applications.

Properties

Density (g/cm ³)	1.18 – 1.22
Energy (MJ/kg)	2.67
Gas Volume (lt/kg)	1041
Detonation Temperature (°C)	1773
V.O.D. (m/s)	5500 – 6000*
Water Resistance	Excellent
Shelf Life	6 Months
Extreme Temperatures	-10°C / +40 °C

* 50mm plastic cartridge, min diameter

* 125mm plastic cartridge

** All values may variate by ± %3

Hazardous Shipping Description

U.N. No: 0332 Class 1.5D
Explosive, Blasting Type E



CE 1019



Nobelex® 1200

Technical
Information



Booster Sensitive Emulsion Explosive

Firing/Initiation

In order to obtain high performance from NOBELEX® 1200, the explosive shall be started with sufficient amount of cap sensitive POWERMITE®.

Handling

The product must be transported in accordance with local and national regulations or directives / guidelines from authorities. No smoking, fire, sparks or welding. Must not be transported with flammable substances.

Storage

Store in cool, dry, well-ventilated location. Store in compliance with local and national regulations or directives/guidelines from authorities. Recommended storage temperature: from - 10 °C to + 40 °C. No smoking, fire, sparks or welding. Must not be stored with flammable substances and ignition sources. Keep away from strong shock.

Safety Instructions

If not stored, handled or used properly, explosives may cause harm to humans or the environment. All types of explosives shall be stored, handled and used in compliance with laws and regulations.

If emulsion explosives;

- are swallowed; do not try to vomit, drink 1 or 2 glasses of water.
- are smeared on eye; wash eyes with water at least for 15 minutes. If disturbance continues seek medical help.
- are spilled on clothes; carefully remove the clothing; make sure the clothes are cleaned before wearing again.

Product Disclaimer. Nitromak DNX A.Ş. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Nitromak DNX A.Ş. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

PACKAGING - CARTRIDGE

Cartridge Diameter (mm)	50	60	75	90
Cartridge Length (mm)	520-530	510-520	510-520	500-510
Cartridge Weight (g)	1250	1820	2860	4000
No. Of Cartridge / Box	16	11	7	5
Box Weight (kg)	20	20	20	20
Case Dimensions (mm)	540x180x250	540x180x250	540x180x250	540x180x250

± %3 Tolerance

This product can be delivered in different package sizes per customer request

PACKAGING - BULK

Weight of Product / IBC tank (kg)*	1000
Package Dimensions (mm)	1200x1000x1160
Weight of IBC (kg)	50

± %3 Tolerance